



<p>FEATURES</p>	<p>: THINNER NO.51 is a high quality thinner for reducing or diluting the TOA Vinyl Anti-Fouling Paint</p> <p>It is specially formulated to give the coating the optimum performance—promoting easy application, so that flows out smoothly without brushmark and developing maximum gloss and depth of finish film</p> <p>: It is suitable for reducing TOA Vinyl Anti-Fouling Paint</p>
<p>TECHNICAL INFORMATION</p> <p>Type</p> <p>Color</p> <p>Specific gravity</p> <p>Flash point</p>	<p>: Thinner</p> <p>: Clear</p> <p>: 0.8 ± 0.02</p> <p>: 20° C</p>
<p>HANDLING AND STORAGE</p> <p>Storage condition</p> <p>Shelf life</p> <p>Package</p>	<p>: The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition.</p> <p>: 60 months at 30–35 °C</p> <p>: The product must be stored in accordance with national regulations. Storage conditions are to keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed.</p> <p>: 1 Gallon and ¼ Gallon</p>
<p>HEALTH AND SAFETY</p>	<p>: Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.</p> <p>: For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Safety Data Sheet.</p>
<p>DISCLAIMER</p>	<p>: The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.</p>