

- Stir well before use
- Apply TOA Acrylic Wall Putty with trowel where needed.
- Plaster with TOA Acrylic Wall Putty and leave to dry prior to applying another coat.
- Sand the surface when dry with sandpaper for more smoothness.
- Apply TOA Alkali Resisting Primer 1 coat.
- Apply 2 coats of paint.

| | |
|--|--|
| Recommendation : | <ul style="list-style-type: none"> - The surface must be dried prior to apply. - Do not use this product while raining. - The crack must be sealed before the primary coat. - Do not apply one time for high thickness, TOA Acrylic Wall Putty must be applied for several layers. - Wash all tools immediately after use with water. |
| USAGE RATE | : 0.5 - 1.5 kg / m ² / 1 mm. thickness |
| HANDLING AND STORAGE Storage Shelf life | <ul style="list-style-type: none"> - Keep all containers well closed. - Keep in a dry cool place. : 12 months in original packing. |
| PACKAGING | : 5 kgs., 25 kgs.container |
| HEALTH AND SAFETY | <p>: Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.</p> <p>: For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.</p> |
| DISCLAIMER | : This information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However,as the product is often used under conditions beyond our control,we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice. |