

FEATURES

Homecote Emulsion Paint use an acrylic emulsion which is specially formulated for use on interior. Does not contain mercury and lead so it would be safe to your health and stays clean for longer and suitable for save cost.

It is ideal for application interior concretes,new and old masonry surfaces,plasters,bricks, asbestos shingled and siding.

TECHNICAL INFORMATION

Type	: Acrylic Emulsion.
Color	: Wide range of colours. Please refer to colour card.
Film appearance	: Matt
Solid by volume	: 31 – 33 %
Solid by weight	: 52 – 54 %
Wet film thickness	: 100-110 microns
Dry film thickness	: 30-35 microns
Theoretical coverage.	: 35-40 sq.m. / gallon / coat

Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated.

Touch dry (25-30°C)	20-30	minutes.
Recoat dry (25-30°C)	2	hours.

REFERENCE STANDARD

-

APPLICATION

Tools	: Brush, roller , spray gun
Thinner	: Clean Water
Dilution (%)	: For rolling, dilute with 10-15% clean water by volume : For brush, dilute with 15-20% clean water by volume : For spray, dilute with 20-25% clean water by volume

APPLICATION SYSTEM

Surface Preparation

Old surface

: Powdery and chalky surface must be scrubbed and cleaned with water
 : Fungus and mildew growth must be cleaned off. Left to dry for 2-3 days.
 : Areas where the fungus to kill mold polished clean with liquid TOA Microkill. Cleaning. Then let it dry 1-2 days.
 : At a crack width less than 1 mm. and not break continuity Putty for filling with TOA acrylic acrylic filler.
 : Around the crack. Wider than 1 mm. or a different continuity. Putty for filling with TOA Acrylic Sealant.

New surface

: Substrate must be completely cured and dried (~1 month) free from oil, grease,mildrew, from release agent and foreign matters
 : For more smooth surface use TOA Acrylic Wall Filler

Coating system

Old Surface/Primer	: Apply 1 coat of Supertech Contact Primer SP 1100
New Surface/Primer	: Apply 1 coat of Homecote Alkali Resisting Primer
Topcoat	: Apply 2 coats of Homecote Interior Emulsion Paint.



HANDLING AND STORAGE

Storage condition

: The product must be stored in accordance with national regulations.

Keep the containers in a dry, cool, well ventilated space and away from source of heat and ignition.

Containers must be kept tightly closed.

Shelf life

: 5 years from producing at 30-35 °C

HEALTH AND SAFETY

: Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

: For detailed information on the health and safety hazards and precautions for use of this product, we refer to the Material Safety Data Sheet.

DISCLAIMER

: The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything only the quality of the product itself. We reserve the right to change the given data without notice.